



Structural Summarization of Semantic Graphs

Ioana Manolescu

► To cite this version:

Ioana Manolescu. Structural Summarization of Semantic Graphs. Extended Semantic Web Conference (ESWC) , Jun 2018, Heraklion, Greece. . hal-01808737

HAL Id: hal-01808737

<https://inria.hal.science/hal-01808737>

Submitted on 6 Jun 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Structural Summarization of Semantic Graphs

Ioana Manolescu

Head of CEDAR team

INRIA and Ecole Polytechnique, France

`ioana.manolescu@inria.fr`

`http://pages.saclay.inria.fr/Ioana.Manolescu`

ESWC Conference, June 5, 2018

Outline

- 1 **Motivation:** **data discovery** in semantic-rich RDF graphs
- 2 **Framework:** **quotient summaries**
 - Smaller graph which represents the original one in some sense
- 3 **Proposal:** use **property cliques** for summarizing **explicit** and **implicit** data
- 4 Summarization **algorithms**
- 5 Perspectives

Joint work with François Goasdoué (U. Rennes 1 and Inria), Paweł Guzewicz (U. Paris Saclay and Inria), and Šejla Čebirić (U. Paris Saclay and Inria) [ČGM15a, ČGM15b, ČGM17a, GM18, PGA⁺18]

Part I

Motivation: data discovery in RDF graphs

Big Data needs semantics


AI Magazine, Spring 2015



The image displays two side-by-side screenshots of the DATA.GOV website, illustrating the application of semantics in big data search. Both screenshots show the 'DATA CATALOG' interface with a search filter set to 'Location' and a map of the United States. The left screenshot shows search results for 'Natural Disaster', listing 93 datasets found. The right screenshot shows search results for 'Earthquakes', listing 243 datasets found. Both results sections include a 'Dataset Type' filter and a 'Show More Dataset Type' link. The results are organized into sections with titles and descriptions, such as 'FEMA Disaster Declarations Summary', 'Noninsured Crop Disaster Assistance Program', 'Child Nutrition Programs Disaster Response Menu', 'Earthquake Feeds', 'Earthquake Locations', and 'Earthquake Damage - General'.

RDF graph discovery

An RDF graph can be large and complex, lack a fixed schema, include many heterogeneous values...



RDF summaries

Simplified views of an RDF graph [ČGK⁺18]

- Most often, a summary is also a **graph**, and/or: **statistics**, **patterns**...
- Summarize: the **data**, the **ontology**, **both**
- Many prior works on graph summarization applied to RDF

RDF summaries

Simplified views of an RDF graph [ČGK⁺18]

- Most often, a summary is also a **graph**, and/or: **statistics, patterns...**
- Summarize: the **data**, the **ontology**, **both**
- Many prior works on graph summarization applied to RDF


Summary uses:

- 1 For **query processing**: give direct access to a group of nodes summarized together, detect empty queries...
- 2 For **data discovery**: help identify interesting structure or patterns in the data

RDF graphs are often structurally heterogeneous


Subject types in DBLP bibliographic data:

Type distribution (Click *All Subjects* or a certain type below for further exploration.)



RDF graphs are often structurally heterogeneous

Data properties of DBLP conference articles:





Our goal

Define **structural summaries** which:

- resist to **heterogeneity**
- flexibly take into account **RDF types**
- allow summarizing **implicit triples**
- can be **implemented efficiently**

The Resource Description Framework (RDF)


RDF graph: set of triples



RDF Schema

We consider **RDFS** deductive constraints, stating connections between classes and properties

Constraint	Triple	OWA interpretation
Subclass	$c_1 \text{ rdfs:subClassOf } c_2$	$c_1 \subseteq c_2$
Subproperty	$p_1 \text{ rdfs:subPropertyOf } p_2$	$p_1 \subseteq p_2$
Domain typing	$p \text{ rdfs:domain } c$	$\Pi_{\text{domain}}(p) \subseteq c$
Range typing	$p \text{ rdfs:range } c$	$\Pi_{\text{range}}(p) \subseteq c$




“Any c_1 is also a c_2 ”

RDF Schema

Simple language of deductive constraints between classes and properties

Constraint	Triple	OWA interpretation
Subclass	$c_1 \text{ rdfs:subClassOf } c_2$	$c_1 \subseteq c_2$
Subproperty	$p_1 \text{ rdfs:subPropertyOf } p_2$	$p_1 \subseteq p_2$
Domain typing	$p \text{ rdfs:domain } c$	$\Pi_{\text{domain}}(p) \subseteq c$
Range typing	$p \text{ rdfs:range } c$	$\Pi_{\text{range}}(p) \subseteq c$




“If two resources are related by p_1 , they are also related by p_2 ”

RDF Schema

Simple language of deductive constraints between classes and properties

Constraint	Triple	OWA interpretation
Subclass	c_1 rdfs:subClassOf c_2	$c_1 \subseteq c_2$
Subproperty	p_1 rdfs:subPropertyOf p_2	$p_1 \subseteq p_2$
Domain typing	p rdfs:domain c	$\Pi_{\text{domain}}(p) \subseteq c$
Range typing	p rdfs:range c	$\Pi_{\text{range}}(p) \subseteq c$




“Anyone having p is a c ”

RDF Schema

Simple language of deductive constraints between classes and properties

Constraint	Triple	OWA interpretation
Subclass	c_1 rdfs:subClassOf c_2	$c_1 \subseteq c_2$
Subproperty	p_1 rdfs:subPropertyOf p_2	$p_1 \subseteq p_2$
Domain typing	p rdfs:domain c	$\Pi_{\text{domain}}(p) \subseteq c$
Range typing	p rdfs:range c	$\Pi_{\text{range}}(p) \subseteq c$



“Anyone who is a value of p is a c ”

Open-world assumption and RDF entailment


RDF data model based on the open-world assumption.

Deductive constraints lead to **implicit triples**:
part of the graph even though not explicitly present

Open-world assumption and RDF entailment

RDF data model based on the open-world assumption.


Deductive constraints lead to **implicit triples**:
part of the graph even though not explicitly present



Open-world assumption and RDF entailment

RDF data model based on the open-world assumption.


Deductive constraints lead to **implicit triples**:
part of the graph even though not explicitly present




Exhaustive application of entailment leads to **saturation (closure)**

The semantics of an RDF graph G is its saturation G^∞

RDF data graph and RDF schema graph:



Saturation of the graph union:



Part III

RDF summarization

RDF summaries

Problem

RDF graph G is large, heterogeneous, partially implicit.
How to compactly represent all its structure?


Existing solutions

Partial representation (frequent patterns, statistics etc.)
e.g., [NM11, LYL13]

Potentially not compact e.g., [GW97, CFKP15]
Only for **explicit data**, e.g., [CDT13, ZDYZ14]

A summary of DBLP data


150M triples



A summary of geographic data

French territory division in regions, departments, urban areas, cities, districts etc.

368K triples



Dataset: <http://inec-gis.fr>. Number of triples: 368417
 Nodes: 30 (Typed: 9, Untyped: 21, Property: 0)
 Edges: 69 (Data edges: 69, Schema edges: 0)

Summarization principle: quotient graphs

Let \equiv be an equivalence relation on the nodes of G .

The **quotient G_{\equiv} of a directed graph G by \equiv** is a graph defined as follows:

- G_{\equiv} nodes: one for \equiv equivalence class of V
- G_{\equiv} edges: $n_{\equiv}^1 \xrightarrow{a} n_{\equiv}^2$ iff $\exists n_1 \xrightarrow{a} n_2 \in G$ such that n_1 represented by n_{\equiv}^1 , n_2 represented by n_{\equiv}^2

Summarization principle: quotient graphs

Let \equiv be an equivalence relation on the nodes of G .

The **quotient G_{\equiv} of a directed graph G by \equiv** is a graph defined as follows:

- G_{\equiv} nodes: one for \equiv equivalence class of V
- G_{\equiv} edges: $n_{\equiv}^1 \xrightarrow{a} n_{\equiv}^2$ iff $\exists n_1 \xrightarrow{a} n_2 \in G$ such that n_1 represented by n_{\equiv}^1 , n_2 represented by n_{\equiv}^2

Quotients have interesting summary qualities:

- 1 **Property completeness:** All G properties appear in G_{\equiv}
- 2 **Size guarantees:** By definition, G_{\equiv} is at most as large as G (usually much smaller)
- 3 **Structure representativeness:** Given a query q , if its **structure-only** version is empty on G_{\equiv} , then q is empty on G

Common graph quotients: bisimilarity [HHK95]

Two nodes are forward (resp. backward) bisimilar if they have exactly the same incoming (resp. outgoing) paths; \sim_{fw} , \sim_{bw} , \sim_{fb}

Common graph quotients: bisimilarity [HHK95]

Two nodes are forward (resp. backward) bisimilar if they have exactly the same incoming (resp. outgoing) paths; \sim_{fw} , \sim_{bw} , \sim_{fb}

Problem: Bisimilarity compresses/summarizes very little!

Common graph quotients: bisimilarity [HHK95]

Two nodes are forward (resp. backward) bisimilar if they have exactly the same incoming (resp. outgoing) paths; \sim_{fw} , \sim_{bw} , \sim_{fb}

Problem: Bisimilarity compresses/summarizes very little!


Solution: Bounded bisimilarity, e.g., \sim_{1fb} (the weakest)

Common graph quotients: bisimilarity [HHK95]

Two nodes are forward (resp. backward) bisimilar if they have exactly the same incoming (resp. outgoing) paths; \sim_{fw} , \sim_{bw} , \sim_{fb}

Problem: Bisimilarity compresses/summarizes very little!

Solution: Bounded bisimilarity, e.g., \sim_{1fb} (the weakest)




Still: > 130 property combinations on conf. papers in DBLP

Common graph quotients: bisimilarity [HHK95]

Two nodes are forward (resp. backward) bisimilar if they have exactly the same incoming (resp. outgoing) paths; \sim_{fw} , \sim_{bw} , \sim_{fb}

Problem: Bisimilarity compresses/summarizes very little!

Solution: Bounded bisimilarity, e.g., \sim_{1fb} (the weakest)



Still: > 130 property combinations on conf. papers in DBLP


Requirement 1: We need equivalence relationships robust to structural heterogeneity.

What about type and schema triples?

Can we apply quotientization directly to an RDF graph?


What about type and schema triples?

Can we apply quotientization directly to an RDF graph?
 Sample graph G and a possible quotient:



What about type and schema triples?


Can we apply quotientization directly to an RDF graph?
Sample graph G and a possible quotient:



Possible loss of class and property names

What about type and schema triples?


Can we apply quotientization directly to an RDF graph?
 Sample graph G and a possible quotient:



Possible loss of schema triples

What about type and schema triples?


Can we apply quotientization directly to an RDF graph?
Sample graph G and a possible quotient thereof:



Possible loss of implicit triples

What about type and schema triples?

Can we apply quotientization directly to an RDF graph?
Sample graph G and a possible quotient thereof:



Possible loss of implicit triples

Requirement 2: Avoid schema loss through quotientization

RDF equivalence relation and RDF summaries

To meet Requirement 2, we define:


- ① **RDF equivalence relation:** an equivalence relation on RDF graph nodes such that any class or property node is only equivalent to itself
- ② **RDF summary:** a quotient of a graph G by an RDF equivalence relation such that any class or property node is represented by itself.

Consequence: For any RDF equivalence relation \equiv and RDF graph G , the schema of $G_{/\equiv}$ is the schema of G .


\Rightarrow No schema compression! (to be rediscussed briefly)

Summarization through an RDF equivalence relation

E.g., let \equiv_{1fb} to be the RDF node equivalence obtained from \sim_{1fb} .
Sample graph G:



Its quotient through the RDF node equivalence \equiv_{1fb} :



Recap

We have seen:

- **RDF node equivalence** and **RDF quotients** \Rightarrow structural representativeness, empty query pruning


We still need to solve:

- **Requirement 1:** compact (yet preserve structure) even on heterogeneous graphs
- **Requirement 3:** can we summarize implicit triples?

We will address them in this order.

RDF node equivalence based on property cliques

Intuition: n_1, n_2 are “of the same kind”; similarly b_1, b_2, b_3




n_3, n_4 may or may not be of the same kind as n_1, n_2 .

RDF node equivalence based on property cliques

Output property cliques: $\{a, b, d\}; \{f\}; \{g\}; \emptyset$


Input property cliques: $\{a\}; \{b\}; \{d\}; \{f\}; \{g\}; \emptyset$



Weak clique-based summaries

Two nodes are weakly equivalent (\equiv_w) iff they have **the same input clique** **or** **the same output clique** **or** are weakly equivalent to a third one.


Weak summary G_w of the sample RDF graph G :



Weak clique-based summaries

Two nodes are weakly equivalent (\equiv_W) iff they have **the same input clique** **or** **the same output clique** **or** are weakly equivalent to a third one.

Weak summary G_W of the sample RDF graph G :




Property: In G_W , each data property appears exactly once \Rightarrow its nodes are “source of p , target of p ” for each p [ČGM15b].

Weak clique-based summaries

Property: G/W nodes are “source of p , target of p ” for each p .

Detecting errors in the data:: why do the birthplace and deathplace loop?



Looking in the data, we find:

```

<http://dbpedia.org/resource/Kunitomo_Ikkansai> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type>
<http://xmlns.com/foaf/0.1/Person> .

```

```


<http://dbpedia.org/resource/Kunitomo_Ikkansai> <http://dbpedia.org/ontology/birthPlace>
<http://dbpedia.org/resource/Kunitomo_Ikkansai> .

```

Strong clique-based summaries

Two nodes are strongly equivalent (\equiv_S) iff they have **the same input clique** **and** **the same output clique**.

Strong summary $G_{/\equiv_S}$ of the same G :



Which role should node types play in summarization?

Having the same type(s) is orthogonal w.r.t. having the same structure.

Which role should node types play in summarization?

Having the same type(s) is orthogonal w.r.t. having the same structure. Two alternatives:


- ① **Data-then-type:** group nodes first by their data triples, then carry the types from each \equiv group to its representative.

Which role should node types play in summarization?

Having the same type(s) is orthogonal w.r.t. having the same structure. Two alternatives:

- 1 **Data-then-type:** group nodes first by their data triples, then carry the types from each \equiv group to its representative.


Extended Weak summary:



Adding types after data summarization

- 1 **Data-then-type:** group nodes first by their data triples, then carry the types from each \equiv group to its representative.


Extended Strong summary:



Giving prominence to types

- Type-then-data:** Group nodes by their type set, and **untyped** nodes by their data properties.


Typed Weak summary $G_{\equiv TW}$ of the sample graph:



Giving prominence to types

- 1 **Type-then-data:** Group nodes first by their types. Only untyped nodes are grouped by their data properties.

Typed Strong summary $G_{\equiv TS}$ of the sample graph:




RDF summaries outline

Summary	Weak?	Strong?	Types first?
$G \equiv W$	✓		
$G \equiv S$		✓	
$G \equiv TW$	✓		✓
$G \equiv TS$		✓	✓

RDF summaries outline

Summary	Weak?	Strong?	FW bisim?	BW bisim?	Types first?
$G \equiv W$	✓				
$G \equiv S$		✓			
$G \equiv TW$	✓				✓
$G \equiv TS$		✓			✓
$G \equiv_{fw}$			✓		
$G \equiv_{bw}$				✓	
$G \equiv_{fb}$			✓	✓	
$G \equiv_{fw,T}$			✓		✓
$G \equiv_{bw,T}$				✓	✓
$G \equiv_{fb,T}$			✓	✓	✓

Relations between RDF summaries [ČGM17b]



Summary size comparison (more in [ČGM17b])

Graph G	$ G $	Summary $G_{/\equiv}$	$ G_{/\equiv} $	cf_{\equiv}
DBLP	150,787,464	$G_{/W}$	71	2,123,767
DBLP	150,787,464	$G_{/S}$	206	731,978
DBLP	150,787,464	$G_{/fw}$	262,695	574
LUBM1M	1,227,868	$G_{/W}$	161	7,579
LUBM1M	1,227,868	$G_{/S}$	207	5,903
LUBM1M	1,227,868	$G_{/fw}$	1982	617
LUBM10M	11,990,183	$G_{/W}$	162	74,013
LUBM10M	11,990,183	$G_{/S}$	206	58,204
LUBM10M	11,990,183	$G_{/fw}$	24,958	480
LUBM10M	11,990,183	$G_{/bw}$	6,162	1,944
LUBM10M	11,990,183	$G_{/fb}$	11,990,076	1

Summarizing G^∞

Recall: With an RDF Schema, the semantics of G is $G^\infty \Rightarrow$
We really need $(G^\infty)_{/\equiv}$!

- 1 Saturate G , then summarize
- 2 Can we avoid saturating G ...

Summarizing G^∞

Recall: With an RDF Schema, the semantics of G is $G^\infty \Rightarrow$
 We really need $(G^\infty)_{/\equiv}$!

- ① Saturate G , then summarize
- ② Can we avoid saturating G ?

Shortcut theorem [ČGM17a]

For the summaries $G_{/\equiv} W$, $G_{/\equiv} S$, $G_{/\equiv} fw$, $G_{/\equiv} bw$, $G_{/\equiv} fb$:

$(G^\infty)_{/\equiv}$ is the same as $((G_{/\equiv})^\infty)_{/\equiv}$

Also: **sufficient condition** for any \equiv to admit the shortcut.

Shortcut path to G^∞


Direct $G \rightarrow \mathbf{sat.} \rightarrow G^\infty \rightarrow \mathbf{summ.} \rightarrow (G^\infty)_\equiv$

Shortcut $G \rightarrow \mathbf{summ.} \rightarrow G_\equiv \rightarrow \mathbf{sat.} \rightarrow (G_\equiv)^\infty \rightarrow \mathbf{summ.} \rightarrow ((G_\equiv)^\infty)_\equiv$


If G_\equiv is much smaller than G , **the shortcut may be faster!**

Up to 20 times in our experiments [ČGM17b]

Shortcut example: $G/\equiv W$



Shortcut counter-example: $G/\equiv \text{TW}$



Summarization algorithms


- 1 **Global algorithms:** visit all G , compute \equiv relation, then traverse G again and represent each triple in $G_{/\equiv} W$
- 2 **Incremental algorithms:** visit G , compute \equiv and summary based on knowledge gained so far; **adjust** summary

We devised global and incremental summarization algorithms for $G_{/\equiv} W$, $G_{/\equiv} S$, $G_{/\equiv} TW$, $G_{/\equiv} TS$.

Difficulty of incremental summarization: adjusting \equiv and revisiting summarization decisions


Example: weak incremental summarization (1)

Each color corresponds to a different \equiv_w class




Example: weak incremental summarization (1)

Each color corresponds to a different \equiv_w class




Example: weak incremental summarization (1)

Each color corresponds to a different \equiv_W class




Example: weak incremental summarization (1)

Each color corresponds to a different \equiv_W class




Example: weak incremental summarization (1)

Each color corresponds to a different \equiv_W class




Example: weak incremental summarization (1)

Each color corresponds to a different \equiv_W class




Example: weak incremental summarization (1)


Each color corresponds to a different \equiv_W class




Example: weak incremental summarization (2)




Example: weak incremental summarization (2)



Example: weak incremental summarization (2)




Example: weak incremental summarization (3)




Example: weak incremental summarization (end)

Full graph and its summary:



Algorithm scale-up


10^5 to 1.5×10^8 triples





Summary-enabled LOD cloud exploration [PGA⁺18]

Collaboration with ILDA Inria data vizualization team on LODAtlas
<http://lodatlas.lri.fr/>

Use summary to derive visualisation instead of the original graph
 (smaller, faster)

abs-linked-data : Australian Bureau of Statistics (ABS) Linked Data 



Part IV

Conclusion

The need for RDF graph discovery tools

- RDF graphs can be **large and complex**, they lack a prescriptive schema
- Semantic rules lead to **implicit data**
- **Structural quotient summaries** compactly represent graph structure and semantics.
Available online at: (new version soon)

<https://team.inria.fr/cedar/projects/rdfsummary/>

- Type-first summarization variant to cope with large type hierarchies [GM18]
- Integration into LODAtlas platform [PGA⁺18]

Part V

Perspectives

Ongoing and future work

Ongoing:

- ① Experiment with new, parallel summarization algorithms based on Spark
- ② Keyword search in RDF graphs based on quotient summaries

Future:

- ① Controlled inclusion of data value synopsis in the summary
- ② Extension to more expressive ontology languages
- ③ Integration in a larger platform for summary-based data discovery (with Mirjana Mazuran)
- ④ Exploration of interesting aggregate view of RDF graphs (with Yanlei Diao)

References

- [CDT13] Stéphane Campinas, Renaud Delbru, and Giovanni Tummarello. Efficiency and precision trade-offs in graph summary algorithms. In IDEAS, 2013.
- [CFKP15] Mariano P. Consens, Valeria Fionda, Shahan Khatchadourian, and Giuseppe Pirrò. S+EPPs: Construct and explore bisimulation summaries + optimize navigational queries (demo). PVLDB, 8(12), 2015.
- [ČGK⁺18] Šejla Čebirić, François Goasdoué, Haridimos Kondylakis, Dimitris Kotzinos, Ioana Manolescu, Georgia Troullinou, and Mussab Zneika. Summarizing semantic graphs: A survey. 2018.
- [ČGM15a] Šejla Čebirić, François Goasdoué, and Ioana Manolescu. Query-oriented summarization of RDF graphs. In BICOD, 2015.
- [ČGM15b] Šejla Čebirić, François Goasdoué, and Ioana Manolescu. Query-oriented summarization of RDF graphs (demonstration). PVLDB, 8(12), 2015.
- [ČGM17a] Šejla Čebirić, François Goasdoué, and Ioana Manolescu. A framework for efficient representative summarization of RDF graphs. In International Semantic Web Conference (ISWC), 2017.
- [ČGM17b] Šejla Čebirić, François Goasdoué, and Ioana Manolescu. Query-Oriented Summarization of RDF Graphs. Research Report RR-8920, INRIA, 2017.

References (cont.)

- [DMS17] Yanlei Diao, Ioana Manolescu, and Shu Shang. Dagger: Digging for interesting aggregates in RDF graphs. In International Semantic Web Conference (ISWC), 2017.
- [GM18] Paweł Guzewicz and Ioana Manolescu. Quotient RDF summaries based on type hierarchies. In Data Engineering for the Semantic Web (DESWeb), 2018.
- [GW97] Roy Goldman and Jennifer Widom. Dataguides: Enabling query formulation and optimization in semistructured databases. In VLDB, 1997.
- [HHK95] Monika Rauch Henzinger, Thomas A. Henzinger, and Peter W. Kopke. Computing simulations on finite and infinite graphs. In FOCS, 1995.
- [LYL13] Shou-De Lin, Mi-Yen Yeh, and Cheng-Te Li. Sampling and summarization for social networks (tutorial), 2013.
- [NM11] Thomas Neumann and Guido Moerkotte. Characteristic sets: Accurate cardinality estimation for RDF queries with multiple joins. In ICDE, 2011.
- [PGA⁺18] Emmanuel Pietriga, Hande Gözükan, Caroline Appert, Marie Destandau, Šejla Čebirić, François Goasdoué, and Ioana Manolescu. Browsing linked data catalogs with LODAtlas. In Int'l. Semantic Web Conference (ISWC), Resources track, 2018.

References (cont.)

- [ZDYZ14] Haiwei Zhang, Yuanyuan Duan, Xiaojie Yuan, and Ying Zhang. ASSG: adaptive structural summary for RDF graph data. In ISWC (Posters and Demonstrations), 2014.